

DMC TREX 250 ROLL

Pull type disc mower conditioner



The **hydraulic shifting** with block valve integrated in the cylinder simplifies the transition from the working position to the transport position with consequent secure locking.



The DMC TREX 250 ROLL can mount the **rubber roller conditioner** for legumes or delicate forages.

DMC TREX 250 ROLL

	Working width	245 cm / 7.8 ft
	Transport width	245 cm / 7.8 ft
	N° of discs	6
	N° of conveyor discs	2
	Cutting height min.	45-90 mm / 1.77-3.54 inch
	Angle of inclination	24°
	Conditioning system	Rollers
	Conditioner speed	830 rpm
	Disc rotational speed	3000 rpm
	Conditioner width	170 cm / 5.6 ft
	Windrow width	65-120 cm / 2.1-4 ft
	Hitch	Drawbar or 2-point hitch
	Tires	340/550-R16
	PTO speed	540 rpm
	Primary PTO	1 3/8"
	Minimum power required	80 HP
	Required tractor hydraulic connection	1 SA and 1 DA
	Machine weight approx.	1650 kg / 3635 lbs
	Safety system between discs against obstacles	•
	Road lights and signaling	•
	Cardan	•

OPTIONAL

DMC TREX 250 ROLL

Protective skids	☒
Quick knife change	☒
Drawbar hitch	☒

• Standard ☒ Optional available - Not available



Via dell'industria, 2 - 06019 Calzolaro di Umbertide (PG) - ITALY
tel. +39 075 930 22 22 - info@enorossi.it - www.enorossi.it

Exclusive Distributor-Asian Market
(India, Bangladesh & Nepal)



Inceptions & Solutions
Driven by Innovations

Zentrum Inagrio Tek

Ganpati Enclave, Humbran Village Gounspur,
Ludhiana 141110, Punjab, India
zentrumindia@gmail.com www.zentrumgroup.in
0091 987 6135 365